LEDER&



BIOTHANE®

OLD - ANTIK



BOVINE HIDES

Origin: Extra European
Average size: 4,00/4,20 m2
Thickness: 1,0 mm +/-

Natural grain

Finishing in Aqueous solution

Alaways available in 13 colours

Article with a natural grain and a characteristic aged effect, obtained with a particular working by through all the characteristics of the leather (wrinkles, scratches, insect bites, veins, etc.) are emphasized; they must be accepted and considered as signs of naturalness and not as defects.

Application: Contract, Public use, Hospitality, Residential.

Fire resistant: UNI EN 1021/1 - UNI EN 1021/2

BS 5852 Source 0, 1 FAR 25853 B

BULLETIN 117 California Test

Physical and colour fastness characteristics		
DRY RUBBING - 800 Cycles	UNI EN ISO 11640	Felt clean
WET RUBBING - 150 Cycles	UNI EN ISO 11640	Felt clean
FINISH ADHESION	UNI EN ISO 11644	> 5 Newton/cm
FLEXING EUNDURANCE - 30.000 Cycles	UNI EN ISO 5402	No surface damage or cracks
COLOUR FASTNESS TO LIGHT	UNI EN ISO 105-B02	> 7 Blue scale
TEAR RESISTANCE	UNI EN ISO 3377-1	> 20 Newton

Chemical characteristics		
Chrome Tannage		
Fatting as established by the Washington Convention		
PCP (Pentachlorophenol), Hexavalent Chrome and Formaldehyde, as for the International law in force		
Azo dyes absent		
REACH (Registration, Evaluation, Authorization and Restriction of Chemicals) √		